

MISCOM8028GX-20GF-8GC

28-port Layer 3 Full Gigabit Rack-mounted Managed Industrial Ethernet Switch



- ◆ Support 8-channel Gigabit Combo optical multiplexing interface, 20-channel 1000Base-LX interface, provide users with flexible networking methods;
- ◆ Support static routing, support RIP v1/v2, OSPF v1/v2 and other dynamic routing protocols;
- ◆ Support IGMP, PIM-SM, PIM-DM and other multicast protocols;
- ◆ High-strength closed aluminum shell, IP40 protection grade, no fan for efficient heat dissipation, so that the system can work reliably in the harsh and dangerous industrial environment of -40~+70°C.



Product Description

MISCOM8028GX series layer 3 full gigabit switches follow the main communication standards in the industrial field and meet technical issues such as real-time communication and network security. At the same time, it provides a variety of ways to manage the switch, including accessing the command line interface (CLI) of the switch through HyperTerminal, or managing the switch through the telnet management system, or using the SNMP management software system to manage the switch, and also supports multiple network monitoring protocols: LLDP, SNTPv4, DHCP. Layer 3 routing also provides advanced management functions such as: MSTP, VRRP, IGMP, IGMP Snooping, internal routing protocols RIPv1/v2 and OSPF v1/v2, static routing protocols, VLAN, GVRP, QoS, port aggregation, port speed limit, broadcast storm suppression, ACL, port mirroring and other common advanced management functions. In terms of device management, it supports FTP/TFTP upgrade, log recording and uploading, and power failure alarm output. In terms of structural installation, you can flexibly choose rack installation or desktop installation. Products are widely used in integrated energy, smart city, rail transit, intelligent transportation, industrial automation and other industrial fields.

Product Features

- ◆ 28 Gigabit Ethernet ports, including 8 Gigabit Combo photoelectric multiplexing ports and 20 1000Base-LX ports, providing users with flexible networking methods;
- ◆ Gigabit SFP interface, which can support hot-swappable SFP optical module and RJ45 electrical port module;
- ◆ The fast ring network redundancy technology of less than 20ms enhances the reliability of system communication;
- ◆ Support VLAN based on IEEE802.1Q, the number is 4096;
- ◆ Support ERPS, MSTP, VRRP and other redundant protocols;
- ◆ Support static routing, support RIP v1/v2, OSPF v1/v2 and other dynamic routing protocols;
- ◆ Support IGMP, PIM-SM, PIM-DM and other multicast protocols;
- ◆ The MAC address table supports 16K;
- ◆ Support perfect QoS strategy and multiple queue scheduling algorithms;
- ◆ Support SNMP, RMON, Telnet and other network management protocols;
- ◆ Support access to the switch's command line interface (CLI) through software such as HyperTerminal;
- ◆ Support hardware ACL function, provide ACL hardware filtering based on L2-L7 layer data;
- ◆ Support IGMP Snooping detection function;
- ◆ Support broadcast storm suppression;
- ◆ Support full-duplex and half-duplex flow control;
- ◆ Support power alarm, port alarm, ring alarm function;
- ◆ The online software upgrade based on FTP/TFTP can facilitate the user's equipment management and update;
- ◆ With graphical network configuration and management and maintenance functions.

Product Specification

Parameters	
IEEE standard	802.3i、802.3u、802.3ab、802.3z、802.3ae、802.3ad、802.3x、802.1p、802.1Q、802.1w、802.1s, etc.
Exchange function	Support VLAN, GVRP
	Support port speed limit, support storm suppression
	Support port aggregation
	Support port flow control
Redundant technology	Support VRRP, ERPS
	Support MW-Ring ring network technology
	Support MSTP/RSTP, compatible with STP
Multicast technology	Support IGMP v1/v2/v3, IGMP Snooping
	Support GMRP
	Support static multicast, support PIM-SM, PIM-DM
Routing technology	Support RIPv1/v2, RIPv6, OSPFv1/v2
	Support static routing protocol
Service quality management	Support ACL to filter L2-L7 layer data
	Support SP, WRR queue scheduling
Management and maintenance	Support Console, Telnet, WEB management, RMON
	Support SNMPv1/v2c/v3, can be centrally managed through MaxView
	Support FTP, TFTP file transfer and software upgrade
	Support power failure alarm, power alarm, port alarm, ring network storm alarm
	Supports port mirroring, Syslog, LLDP, RTC, STMPv4
	IP supports DHCP server/relay/client
Exchange method	store and forward
Backplane bandwidth	56Gbps
Packet forwarding rate	41.664Mpps
Gigabit port	28 1000Base-LX ports Or 8 10/100/1000Base-T+20 1000Base-LX interfaces
Copper port	Physical interface: RJ45 with shielding, IEEE802.3 standard
	RJ45 port: 10/100/1000Base-T (Gigabit) supports auto-negotiation function
	Transmission distance: 100 meters (standard CAT5/CAT5e cable)
Fiber port	Luminous power: >-12dBm (single mode) >-17dBm (multimode)
	Receiver sensitivity: <-38dBm (single mode) <-35dBm (multimode)
	Wavelength: 1310nm (single-mode) 1550nm (single-mode) 850 nm

	(multi-mode) 1310 nm (multi-mode)
	Transmission distance: multimode fiber 850nm, 2km; 1310 nm, 2/5km Single-mode fiber 1310nm, 20/40/60km; 1550nm, 20/40/60/80/120km
	Connector Type: LC
	Transmission rate: 1.25Gbps (Gigabit)
Power	Input voltage: 220AC/DC (85-264VAC/110-370VDC)
	Input power consumption: 40W (MAX)
	Overcurrent Protection: Built-in
Mechanical	Physical dimensions (width × height × depth): 482.6mm × 44mm × 315mm
	Installation method: standard 19' 1U rack
	Heat dissipation form: aluminum alloy single-rib chassis surface heat dissipation, no fan
	Outlet form: front and rear outlet
	Case protection: IP40
Working environment	Working temperature: -40°C~+70°C
	Storage temperature: -40°C~+85°C
	Humidity: 5%~95% (no condensation)
EMC	EN61000-4-2 anti-static (ESD): ±8kV contact discharge, ±15kV air discharge
	EN61000-4-3 electromagnetic field: 10V/m (80-1000MHz)
	EN61000-4-6 anti-conduction: 3V (10kHz~150 kHz), 10V (150kHz~80 MHz)
	EN55022: EN55022 Class A

Ordering Information

Model	1000Base-LX	Gigabit Combo ports	Power
MISCOM8028GX-20GF-8GC-AD220	20	8	Single AC/DC220V
MISCOM8028GX-20GF-8GC-2AD220	20	8	Dual AC/DC220V

